#### **Solid State Drives**

## **TR200**

#### State-of-the-art storage for entry level HDD upgrades



960 480 240 GB GB

Color



Upgrading from a hard drive (HDD) should be easy and affordable and that's where OCZ TR200 SSDs come in. Designed to boost the speed of your notebook or PC over conventional HDDs, the TR200 Series leverages Toshiba's advanced 64-layer 3D BiCS FLASH  $^{\rm TM}$ , to deliver well-balanced performance, reliability, and value that will transform your mobile or desktop system.



5" 2,5-inch

64-layer 3D BiCS FLASH TLC

Sequential Read/Write Speed: Up to 555/540

Random Read/Write Speed (4KiB): Up to 82,000/88,000 IOPS





# **Product Specifications**

Storage memory	64-layer 3D BiCS TLC		
Capacity	240 GB, 480 GB, 960 GB  Grey  Serial ATA (SATA) 6 Gbit/s		
Colours			
Interface			
Form Factor	2.5-inch, 7mm height		
Native Command Queuing (NCQ)	No		
S.M.A.R.T Support	No		
Garbage collection	No		
Read only mode	No No		
Patrol Read			
Thermal control			
MTTF	1.5 Mhours		
Supply Voltage	5V ± 5 %		
DevSleep Power	10 mW max		
Power Consumption	Active Up to 1.7 W (typ.) Idle 100 Mw (typ.)		

Dimensions	100.45 x 69.85 x 7.00 mm			
Weight	240 GB: 45.5g (typ.)			
3	480 GB: 45.6g (typ.)			
	960 GB: 45.7g (typ.)			
Product Health Monitoring	Self-Monitoring, Analysis and			
	Reporting Technology			
	(SMART) Support			
Serial ATA	ATA/ATAPI Command Set-3			
	(ACS-3) and Serial ATA			
	revision 3.2 interface			
	specifications supported			
	Specifications supported			
Operating system	Windows® 10, Windows®			
	8.1, Windows® 7; Linux®			
	Fedora21; Mint 17.1;			
	OpenSUSE 13.2; Ubuntu			
	14.04; Ubuntu 14.10; Mac®			
	OS X® 10.9, 10.10, 10.11			
	03 % 10.3, 10.10, 10.11			
Operating Temperature	0°C to 65°C			
Storage Temperature	-40°C to 85°C			
Shock Resistance	14.7 km/s² {1500 G} (05. ms)			
Vibration (Operational &	196 m/s² {20 Grms} (Peak, 10			
Non-Operational)	to 2,000 Hz)			
Non-Operational)	10 2,000 112)			
Certifications	UL/cUL, FCC, CE, RCM, KC,			
	BSMI, VCCI, and ISED			
Connector Type	Standard SATA connector			
Targeted Applications	Client desktops and laptops			
Doufoumon o Outimis-ti	TRIM, Idle Time Garbagde			
Performance Optimisation	Collection			
Service & Support	3-year Standard Warranty,			
	Toll-Free Tech Support			
Software & Services	SSD management software:			
Solution & Services	SSD Utility and Command Line			
	Online Update Tool (CLOUT)			
	Chinic Opudic 1001 (CLOO1)			

## **Product Range**

Part number	Capacity	Color	EAN
THN-TR20Z2400U8(CS	240 GB	Grey	889661182696
THN-TR20Z4800U8(CS	480 GB	Grey	889661182702
THN-TR20Z9600U8(CS	960 GB	Grey	889661182719

### Contact

#### Toshiba Memory Europe GmbH

Hansaallee 181 40549 Düsseldorf Germany